

UV GUARD EXTERIOR / INTERIOR WOOD FINISH

Version 1.0 Print Date: 05/08/2014

SECTION 1 – PRODUCT IDENTIFICATION

UV Guard Exterior / Interior Wood Finish Trade Name

Product Code 1045-01

Company Weatherall Company, Inc.

106 Industrial Way

Charlestown, IN 47111

(800) 367-7068 8:00 - 5:00 EST Telephone

Emergency Phone (812) 256-3378

Product Use Coating

SECTION 2 – HAZARDS IDENTIFICATION

Emergency Overview

Milky liquid. May cause slight irritation to the respiratory system. Leave area to breathe fresh air. Avoid further exposure. If symptoms persist, get medical attention.

Acute Potential Health Effects / Routes of Entry

May cause slight irritation to the respiratory system. Inhalation

Eves Slightly irritating.

While this product has a low degree of toxicity, ingestion of excessive quantities Ingestion

may cause irritation to the mouth, throat and stomach.

Irritant effect may be delayed. Prolonged or repeated contact with skin can cause Skin

mild irritation, defatting and dermatitis.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

No chronic hazard is anticipated.

Carcinogenicity NTP: IARC MONOGRAPHS: No OSHA REGULATED: No No

SECTION 3 - PRODUCT COMPOSITION - HAZARDOUS COMPONENTS

Chemical Name CAS-No. Weight %

*** NO REPORTABLE QUANTITIES OF HAZARDOUS INGREDIENTS ARE PRESENT. ***

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***



UV GUARD EXTERIOR / INTERIOR WOOD FINISH

Version 1.0 Print Date: 05/01/2007

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation : If irritation of nose or throat develops, remove victim to fresh air. If victim is not

breathing or if breathing is difficult, artificial respiration or oxygen should be administered by qualified personnel. Seek medical attention. If victim is drowsy and unconscious, place on left side with head down. Do not give anything by

mouth. Get medical help.

Eye Contact : Flush with water for 15 minutes. If irritation persists, get medical attention.

Skin Contact : Wash affected area with soap and water. If irritation, rash or any other disorders

develop, get medical attention immediately.

Ingestion : Do not induce vomiting unless advised by a physician.

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point : None Method : Setaflash

Burning Rate : Non-flammable solid Lower Flammable Limit : 1.1% in air by volume Upper Flammable Limit : Not available

Upper Flammable Limit : Not available Autoignition Temperature : Not available

Extinguishing Media : This product is not expected to burn under normal conditions of use. Use that

which is appropriate to the surroundings. Foam, Alcohol Foam, CO₂, Dry

Chemical, Water Fog.

Hazardous Combustion

Products : Smoke, fumes.

Protective Equipment for

Firefighters : Not applicable. Product is not expected to burn.

Fire and Explosion

Conditions : This product is not expected to ignite under normal conditions of use. Closed

containers exposed to very high temperatures may rupture due to pressure

buildup.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Scrape up and transfer to appropriate container for disposal. Keep out of water courses. Dispose of product in accordance with applicable local, county, state and federal regulations.

SECTION 7 – HANDLING AND STORAGE

Prevent inhalation of vapor, ingestion and contact with skin, eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Do not use in confined or poorly ventilated areas. Store in sealed containers in a dry, ventilated area not subject to extremes of temperatures and freezing.



UV GUARD EXTERIOR / INTERIOR WOOD FINISH

Version 1.0 Print Date: 05/01/2007

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal Protection Equipment

Respiratory Protection : Special protection is not required unless the material is sprayed. If sprayed,

adequate ventilation should maintain concentrations below PEL's and prevent inhalation of overspray. Where ventilation is inadequate, us NIOSH approved

resipirator or forced air mask.

Hand Protection : Protect hands under prolonged use with impermeable gloves.

Eye Protection : Approved eye protection to safeguard against potential eye contact is

recommended.

Protective Measures : A source of clean water should be available for flushing of eyes or skin in the

event of an accident. An apron or impervious clothing should be worn as needed.

Engineering Measures : Where large surfaces are coated in a confined area, adequate ventilation should

be provided to prevent buildup of volatile materials above TLV's.

Hygienic Practices : Clean contaminated skin with mild soap and water before material dries. Wash

hands thoroughly before handling food.

Exposure Limits

No known components with exposure limits.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Form : White milky liquid

Odor : Mild monomer odor

pH : 8.0 +/- 0.5

Vapor Density : Lighter than air

Evaporation Rate : Slower than Ether

Water Solubility : Dilutable

Specific Gravity (H2O = 1): 1.0

Boiling Point : 212° F.

Material V.O.C. : 0.38 lb./gal. (46 g/l)



UV GUARD EXTERIOR / INTERIOR WOOD FINISH

Version 1.0 Print Date: 05/01/2007

SECTION 10 – REACTIVITY / STABILITY

Stability : Stable

Conditions to Avoid : None known

Substances to Avoid : No hazardous reactions are expected to occur under normal conditions of use.


Hazardous Decomposition

Or Byproducts : Combustion of the dry film may produce carbon monoxide and/or carbon

dioxide. Oxides of nitrogen

Hazardous Polymerization: Will not occur.

SECTION 11 – OTHER INFORMATION



SECTION 12 - DISCLAIMER

The information and recommendations set forth herein are presented in good faith and believed to be correct as of date. Weatherall Company, Inc. makes no representation as to the completeness or accuracy thereof. Information is supplied under the condition that the recipient will make his/her own determination as to the suitability for the intended purpose, prior to use.

Prepared By: Bobby McBride